



SPECIFICATIONS

Basic Functions	Range	Best Accuracy
Insulation Resistance	500V: 0.1MΩ~60.0MΩ 60MΩ~500MΩ 1000V: 0.1MΩ~60.0MΩ 60MΩ~600MΩ	±(2%+5)
DC Voltage	60mV/600mV/6V/60V/600V/1000V	±(0.09%+2)
AC Voltage	6V/60V/600V/1000V	±(1%+3)
DC Current	60mA/400mA	±(0.2%+2)
AC Current	60mA/400mA	±(1.5%+2)
Resistance	600Ω/6KΩ/60KΩ/600KΩ/6MΩ/40MΩ	±(0.9%+2)
Capacitance	10nF/100nF/1μF/10μF/100μF	±(1%+3)
Frequency	60Hz/600Hz/6KHz/60KHz/600KHz/1MHz	±(0.1%+1)
Special Functions		
Auto Ranging	✓	
Diode	✓	
Continuity Buzzer	✓	
True RMS	✓	
Data Hold	✓	
Data Logging	99	
Data Recall	✓	
Full Icon Display	✓	
Display Backlight	✓	
Max / Min Mode	✓	
Zeroing	✓	
Sleep Mode	✓	
Low Battery Display	✓	

GENERAL CHARACTERISTICS

Power	1.5V Battery(LR16)×6
LCD Size	72×43 mm
Product Color	Red and Grey
Product Net Weight	505g
Product Size	97×202×46mm
Standard Accessories	Test Lead, Batteries, English Manual, Alligator Clips
Standard Individual Packing	Gift Box
Standard Quantity Per Carton	20pcs
Standard Carton Measurement	530×360×385mm (0.073CBM Per Standard Carton)
Standard Carton Gross Weight	24 kg

*Available at Extra Cost

Specifications and other information are subject to change without further notice.